

RT

RUBBER TYRE | CAST IRON CENTRE



WHEELS

wheel diameter	tread width	hub width	bore diameter	load capacity	used in castor series	ball bearing
150	50	60	20	400	VSL VSH 2VSH	G 150 RTJ 20
200	50	60	20	600	V50Q VSL VSH 2VSH	G 200 RTJ 20
250	50	60	25	680	VSH 2VSH	G 250 RTJ 25
300	50	60	25	750		G 300 RTJ 25



CI

CAST IRON



WHEELS

wheel diameter	tread width	hub width	bore diameter	load capacity	used in castor series	ball bearing
100	50	60	20	450	V50Q VSL VSH 2VSH	G 100 CIJ 20
125	40	60	20	630	V50Q VSL VSH 2VSH	G 125 CIJ 20
150	45	60	20	1180	V50Q VSL VSH 2VSH	G 150 CIJ 20
200	45	60	20	1270	V50Q VSL VSH 2VSH	G 200 CIJ 20
250	50	60	25	1360	V50Q VSH 2VSH	G 250 CIJ 25



i All dimensions are in **mm** and all loadings are in **kg** unless otherwise stated

HEAD OFFICE & WAREHOUSE: 5 CENTURY PARK PACIFIC ROAD BROADHEATH ALTRINCHAM CHESHIRE WA14 5BJ t: 0161 928 9617 f: 0161 928 7824 e: SALES@VARLEY.CO.UK
MIDLANDS, SOUTH t: 01952 462527 f: 01952 460176 e: MIDSALLES@VARLEY.CO.UK

