


2ST 2FT



- Twinwheel
- Top plate fixing
- Kingpinless swivel head design



2ST + CAST NYLON WHEEL (not illustrated)

wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type			swivel + thumbscrew wheel brake	swivel + 4 way directional lock
						swivel	fixed		
200	75 x 2	268	132	5080	ball	2ST 200 CN2 75	2FT 200 CN2 75	2ST 200 CN2 75 W	2ST 200 CN2 75 D
250	75 x 2	319	129	5080	ball	2ST 250 CN2 75	2FT 250 CN2 75	2ST 250 CN2 75 W	2ST 250 CN2 75 D
300	75 x 2	369	129	5080	ball	2ST 300 CN2 75	2FT 300 CN2 75	2ST 300 CN2 75 W	2ST 300 CN2 75 D

2ST + POLYURETHANE TYRED WHEEL WITH CAST IRON CENTRE

wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type			swivel + thumbscrew wheel brake * **	swivel + 4 way directional lock **
						swivel	fixed		
200	75 x 2	268	132	3060	taper roller	2ST 200 PTTC	2FT 200 PTTC	2ST 200 PTTC W	2ST 200 PTTC D
250	75 x 2	319	129	4250	taper roller	2ST 250 PTTC	2FT 250 PTTC	2ST 250 PTTC W	2ST 250 PTTC D
300	75 x 2	369	129	4675	taper roller	2ST 300 PTTB	2FT 300 PTTB	2ST 300 PTTB W	2ST 300 PTTB D

* Thumbscrew fitted to each side of twinwheel swivel castors.

** Thumbscrew adaptation is available fitted to castors with directional lock. To order add W to castor reference.

NOTE: All dimensions are in mm and all loadings in kg unless otherwise stated