


2V30V

2V32V




- Double ball race swivel head
- Top plate or bolt hole fixing

VARLEY




2V30V + POLYPROPYLENE WHEEL - PLATE FIXING



| wheel diameter | tread width | fitted height | swivel offset | load capacity | bearing type | bearing type | | |
|----------------|-------------|---------------|---------------|---------------|--------------|-------------------|-------|---------------------------|
| | | | | | | swivel | fixed | swivel + total stop brake |
| 50 | 18 x 2 | 71 | 32 | 60 | plain | 2V30V 050 POP P01 | | 2V32V 050 POP P01 |
| 75 | 23 x 2 | 103 | 32 | 90 | plain | 2V30V 075 POP P01 | | 2V32V 075 POP P01 |

2V30V + POLYPROPYLENE WHEEL - BOLT HOLE FIXING



| wheel diameter | tread width | fitted height | swivel offset | load capacity | bearing type | bearing type | | |
|----------------|-------------|---------------|---------------|---------------|--------------|-------------------|-------|---------------------------|
| | | | | | | swivel | fixed | swivel + total stop brake |
| 50 | 18 x 2 | 71 | 30 | 60 | plain | 2V30V 050 POP B10 | | 2V32V 050 POP B10 |
| 75 | 23 x 2 | 100 | 32 | 90 | plain | 2V30V 075 POP B10 | | 2V32V 075 POP B10 |



EXPANDING ADAPTOR for round or square tubing
To suit all bolt hole fixing castors. See page 4

NOTE: All dimensions are in mm and all loadings in kg unless otherwise stated