

- Single ball race
- Top plate fixing

61 + POLYURETHANE TYRED WHEEL WITH CAST IRON CENTRE



75mm swivel

- 105 x 80mm
- ◇ 86 x 60mm
- ◇ 80 x 60mm
- ⚙ M8

75mm fixed

- 102 x 64mm
- ◇ 83 x 35mm
- ⚙ M8

100mm swivel

- 128 x 102mm
- ◇ 105 x 80mm
- ◇ 100 x 76mm
- ⚙ M10

100, 125mm fixed

- 121 x 80mm
- ◇ 100 x 48mm
- ⚙ M10


125, 150mm swivel

- 162 x 133mm
- ◇ 140 x 105mm
- ◇ 120 x 95mm
- ⚙ M10


150mm fixed

- 155 x 113mm
- ◇ 133 x 67mm
- ⚙ M10


wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type	swivel	fixed	swivel + wheel brake
75	29	95	24.5	150	plain	3 61 SU	3 88 SU	3 61 SU BR
100	43	125	26	295	roller	4 61 SUB	4 88 SUB	4 61 SUB BR
125	35	156	35.5	325	roller	5 61 SUB	5 88 SUB	
150	38	181	42	540	roller	6 61 SUB	61 88 SUB	



THREADED STEM to suit
75mm swivel castors
Add ST to castor reference



- 140 x 140mm
- ◇ 73-102 x 73-102mm
- ⚙ M8



- 150 x 150mm
- ◇ 96-114 x 96-114mm
- ⚙ M10

TRIANGULAR TOP PLATE to suit
75, 100mm swivel castors
Add V to castor reference

NOTE: All dimensions are in mm and all loadings in kg unless otherwise stated