

	wheel diameter	tread width	hub width	bore diameter	load capacity	used in castor series	ball bearing
P	100	40	40	15	300	V50A VSL VSH 2VSH	A 100 NYJ 15 HD
P	125	45	50	20	400	V50A VSL VSH 2VSH	A 125 NYJ 20 HD
P	150	50	55	20	500	VSL	A 150 NYJ 20 HD
P		50	60	20	800	VSH 2VSH	150 NY2H
P	160	50	55	20	500	V50A	A 160 NYJ 20 HD
P	200	57	60	25	800	V50A VSL	A 200 NYJ 25 HD
P		50	60	25	1500	VSH 2VSH	200 NY2H
P	250	50	60	25	1500	VSH 2VSH	250 NY2H



	wheel diameter	tread width	hub width	bore diameter	load capacity	used in castor series	ball bearing
P	100	40	40	15	300	V50A VSL VSH 2VSH	A 100 NPJ 15 - GREY
P	125	45	49	20	400	V50A VSL VSH 2VSH	A 125 NPJ 20 - GREY
P	150	50	55	20	500	VSL VSH 2VSH	A 150 NPJ 20 - GREY
P	160	50	55	20	500	V50A	A 160 NPJ 20 - GREY
P	200	57	60	20	800	V50A VSL VSH 2VSH	A 200 NPJ 20 - GREY



	wheel diameter	tread width	hub width	bore diameter	load capacity	used in castor series	ball bearing
P	100	40	40	15	160	V50A	A 100 ARJ 15
P		40	45	20	160	VSL VSH 2VSH	G 100 ARJ 20
P	125	40	50	20	200	V50A	A 125 ARJ 20
P		50	60	20	200	VSL VSH 2VSH	G 125 ARJ 20
P	150	50	60	20	300	VSL VSH 2VSH	G 150 ARJ 20
P	160	50	60	20	350	V50A	G 160 ARJ 20
P	200	50	60	20	400	V50A VSL VSH 2VSH	G 200 ARJ 20
P	250	50	60	25	550	VSH 2VSH	G 250 ARJ 25



P Preferred range product, see page 1 for details

i All dimensions are in mm and all loadings are in kg unless otherwise stated