

# FS

HIGH TEMPERATURE | THERMOPLASTIC | EFFECTIVE RANGE -40°C TO +270°C



SPECIAL APPLICATION WHEELS



wheel diameter	tread width	hub width	bore diameter	load capacity	plain bore	roller bearing	ball bearing
80	30	40	12	150	28002		
<b>P</b> 100	30	40	12	200	28006		
125	35	50	20	250	28010		
150	45	60	20	300	28014		
200	50	60	20	400	28022		



SPECIAL APPLICATION WHEELS



HIGH TEMPERATURE | NON-MARKING BLACK RUBBER TYRE WITH THERMOPLASTIC CENTRE | EFFECTIVE RANGE -40°C TO +250°C

wheel diameter	tread width	hub width	bore diameter	load capacity	plain bore	roller bearing	ball bearing
100	30	40	12	80	27856		



SPECIAL APPLICATION WHEELS



# GB

HIGH TEMPERATURE | NON-MARKING BLUE RUBBER TYRE WITH ALUMINIUM CENTRE | EFFECTIVE RANGE -40°C TO +250°C

wheel diameter	tread width	hub width	bore diameter	load capacity	plain bore	roller bearing	ball bearing
80	32	42	8	80			27005PF
100	35	42	8	100			27007PF



**P** Preferred range product, see page 1 for details

**i** All dimensions are in **mm** and all loadings are in **kg** unless otherwise stated

