

- o Contemporary design
- o Corrosion resistant polyamide construction
- o Bolt hole fixing
- o Precision ball bearing in swivel head
- o Labyrinth seal for protection in wet conditions



i Only ball bearing wheels are fitted with threadguards




TANGO + THERMOELASTIC RUBBER TYRED WHEEL WITH POLYPROPYLENE CENTRE - BOLT HOLE FIXING

wheel diameter	tread width	fitted height	swivel offset	shore A	load capacity	bearing type	swivel	fixed	swivel + total stop brake	swivel + directional lock
75	32	110	35.5	80	70	plain	MK-75 PTE 80		MK-J-75 PTE 80	
	32	110	35.5	80	70	ball	MK-S-75 PTE/K 80		MK-J-S-75 PTE/K 80	
100	32	141	45	55	70	plain	GK-100 PTE 55		GK-J-100 PTE 55	
	32	141	45	55	70	ball	GK-S-100 PTE/K 55		GK-J-S-100 PTE/K 55	
	32	141	45	80	100	ball	GK-S-100 PTE/K 80		GK-J-S-100 PTE/K 80	
	32	141	45	90	110	ball	GK-S-100 PTE/K 90		GK-J-S-100 PTE/K 90	
125	32	161	44.5	55	70	plain	GK-125 PTE 55		GK-J-125 PTE 55	
	32	161	44.5	55	70	ball	GK-S-125 PTE/K 55		GK-J-S-125 PTE/K 55	
	32	161	44.5	80	100	ball	GK-S-125 PTE/K 80		GK-J-S-125 PTE/K 80	
	32	161	44.5	90	110	ball	GK-S-125 PTE/K 90		GK-J-S-125 PTE/K 90	

TANGO + ELASTIC RUBBER TYRED WHEEL WITH NYLON CENTRE - BOLT HOLE FIXING

wheel diameter	tread width	fitted height	swivel offset	shore A	load capacity	bearing type	swivel	fixed	swivel + total stop brake	swivel + total stop brake
100	32	141	45	60	80	ball	GK-S-100 NEK/K		GK-J-S-100 NEK/K	
125	32	161	44.5	60	100	ball	GK-S-125 NEK/K		GK-J-S-125 NEK/K	



◀ ALTERNATIVE BOLT HOLE SIZE to suit 12m bolt.

Available on all castors.

When fitting an M12 bolt, access is restricted. It is therefore recommended that the bolt be fitted from above with nut and washer underneath swivel head.

Add -12 to castor reference.

▶ SEALED, STAINLESS STEEL BEARING in swivel head. Includes stainless steel wheel bearing (for ball bearing wheels) and all other metal components in stainless steel.

Available on all 100, 125mm castors with 80 shore A.

Add -IX to castor reference.



i All dimensions are in mm and all loadings in kg unless otherwise stated