


STAINLESS
medium duty
I20
continued




- Stainless steel
- Plastic swivel seal




I20 + Polyurethane tyred wheel with nylon centre - plate fixing



80, 100, 125mm



150, 200mm




wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type	swivel	fixed	swivel + total stop brake
80	25	106	33	100	plain	21127	21177	21127 FR
100	30	128	37	150	plain	21130	21180	21130 FR
125	30	154	40	150	plain	21131	21181	21131 FR
	30	160	49	230	roller	21107	21157	21107 FR
150	40	181	51	250	roller	21111	21161	21111 FR
200	50	240	59	370	roller	21117	21167	21117 FR

I20 + Polyurethane tyred wheel with nylon centre - bolt hole fixing



M12 BOLT HOLE is also available.

Replace **HA** with **HB** in castor code.



wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type	swivel	fixed	swivel + total stop brake
80	25	106	33	100	plain	21227HA		21227HA FR
100	30	128	37	150	plain	21230HA		21230HA FR
125	30	154	40	150	plain	21231HA		21231HA FR

NOTE: All dimensions are in mm and all loadings in kg unless otherwise stated