

# M22HT




HIGH TEMPERATURE | EFFECTIVE RANGE -40°C TO +270°C | DOUBLE BALL RACE SWIVEL HEAD | SWIVEL HEAD SEAL

SPECIAL APPLICATION CASTORS



## M22HT | FS | PLATE FIXING


THERMOPLASTIC WHEEL



wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type	swivel	fixed	swivel + total-stop brake
80	30	106	33	120	plain	28702	28802	28702 FR
100	30	128	37	120	plain	28706	28806	28706 FR
125	35	160	49	200	plain	28709	28809	28709 FR

## M22HT | FS | SINGLE HOLE FIXING

THERMOPLASTIC WHEEL



Castors with **GB** suffix:

M12

Castors with **GD** suffix:

M14



wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type	swivel	fixed	swivel + total-stop brake
80	30	106	33	120	plain	28902 GB		28902 GB FR
100	30	128	37	120	plain	28906 GB		28906 GB FR
125	35	160	49	200	plain	28910 GD		28910 GD FR



HIGH TEMPERATURE WHEEL

Available separately

See page 61

All dimensions are in **mm** and all loadings are in **kg** unless otherwise stated

HEAD OFFICE & WAREHOUSE: 5 CENTURY PARK PACIFIC ROAD BROADHEATH ALTRINCHAM CHESHIRE WA14 5BJ t: 0161 928 9617 e: SALES@VARLEY.CO.UK  
MIDLANDS, SOUTH t: 01952 462527 e: MIDSALSALES@VARLEY.CO.UK

