

# M22HT




HIGH TEMPERATURE | EFFECTIVE RANGE -40°C TO +270°C | DOUBLE BALL RACE SWIVEL HEAD | SWIVEL HEAD SEAL

SPECIAL APPLICATION CASTORS



## M22HT | FS | PLATE FIXING


THERMOPLASTIC WHEEL



	wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type	swivel	fixed	swivel + total-stop brake
<b>P</b>	80	30	106	33	120	plain	28702	28802	28702 FR
<b>P</b>	100	30	128	37	120	plain	28706	28806	28706 FR
<b>P</b>	125	35	160	49	200	plain	28709	28809	28709 FR

## M22HT | FS | SINGLE HOLE FIXING

THERMOPLASTIC WHEEL



Castors with **GB** suffix:

M12

Castors with **GD** suffix:

M14



	wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type	swivel	fixed	swivel + total-stop brake
<b>P</b>	80	30	106	33	120	plain	28902 GB		28902 GB FR
<b>P</b>	100	30	128	37	120	plain	28906 GB		28906 GB FR
<b>P</b>	125	35	160	49	200	plain	28910 GD		28910 GD FR



HIGH TEMPERATURE WHEEL

Available separately

Please ask for details

**P** Preferred range product, see page 1 for details

**i** All dimensions are in **mm** and all loadings are in **kg** unless otherwise stated

