



V22 | RN | PLATE FIXING



BLUE RUBBER TYRED WHEEL WITH NYLON CENTRE



	wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type	swivel	fixed	swivel + total-stop brake
P	100	36	132	39	160	roller	V 422 RNB	V 429 RNB	V 422 RNB SWB
P	125	37	155	39	180	roller	V 522 RNB	V 529 RNB	V 522 RNB SWB
P	150	50	190	53	300	roller	V 622 RNB	V 629 RNB	V 622 RNB SWB
P	200	50	235	53	450	roller	V 822 RNB	V 829 RNB	V 822 RNB SWB

V22 | PN | PLATE FIXING

RED POLYURETHANE TYRED WHEEL WITH NYLON CENTRE



	wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type	swivel	fixed	swivel + total-stop brake
P	100	36	132	39	250	roller	V 422 PNB	V 429 PNB	V 422 PNB SWB
P	125	36	155	39	250	roller	V 522 PNB	V 529 PNB	V 522 PNB SWB
P	150	50	190	53	500	roller	V 622 PNB	V 629 PNB	V 622 PNB SWB
P	200	50	235	53	500	roller	V 822 PNB	V 829 PNB	V 822 PNB SWB

P Preferred range product, see page 1 for details

i All dimensions are in **mm** and all loadings are in **kg** unless otherwise stated