




VARLEY




- Double ball race swivel head
- Top plate or bolt hole fixing


V30V
V32V

V30V + GREY THERMOPLASTIC RUBBER TYRED WHEEL WITH NYLON CENTRE - PLATE FIXING

50, 75mm




100, 125mm




wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type	fixing		
						swivel	fixed	swivel + total stop brake
50	18	68	23	50	plain	V30V 050 TRP P01		V32V 050 TRP P01
75	23	97	30	70	plain	V30V 075 TRP P01		V32V 075 TRP P01
100	27	132	38	80	plain	V30V 100 TRP P02		V32V 100 TRP P02
125	27	155	42	100	plain	V30V 125 TRP P02		V32V 125 TRP P02

V30V + GREY THERMOPLASTIC RUBBER TYRED WHEEL WITH NYLON CENTRE - BOLT HOLE FIXING

50, 75mm



100, 125mm



wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type	fixing		
						swivel	fixed	swivel + total stop brake
50	18	67	23	50	plain	V30V 050 TRP B10		V32V 050 TRP B10
75	23	95	30	70	plain	V30V 075 TRP B10		V32V 075 TRP B10
100	27	130	38	80	plain	V30V 100 TRP B12		V32V 100 TRP B12
125	27	153	42	100	plain	V30V 125 TRP B12		V32V 125 TRP B12



EXPANDING ADAPTOR for round or square tubing
To suit all bolt hole fixing castors. See page 4

NOTE: All dimensions are in mm and all loadings in kg unless otherwise stated