






VARLEY



- Double ball race swivel head
- Top plate or bolt hole fixing


**V40V**  
V41V V42V

**V40V + BLUE RUBBER TYRED WHEEL WITH NYLON CENTRE - PLATE FIXING**



wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type	fixing		
						swivel	fixed	swivel + total stop brake
80	28	108	36	90	roller	V40V 080 BRR P04	V41V 080 BRR P04	V42V 080 BRR P04
100	30	128	36	120	roller	V40V 100 BRR P04	V41V 100 BRR P04	V42V 100 BRR P04
125	36	151	36	170	roller	V40V 125 BRR P04	V41V 125 BRR P04	V42V 125 BRR P04
160	46	197	55	300	roller	V40V 160 BRR P05	V41V 160 BRR P05	V42V 160 BRR P05
200	46	235	55	300	roller	V40V 200 BRR P05	V41V 200 BRR P05	V42V 200 BRR P05

**V40V + BLUE RUBBER TYRED WHEEL WITH NYLON CENTRE - BOLT HOLE FIXING**



wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type	fixing		
						swivel	fixed	swivel + total stop brake
100	30	128	36	120	roller	V40V 100 BRR B12		V42V 100 BRR B12
125	36	151	36	170	roller	V40V 125 BRR B12		V42V 125 BRR B12



EXPANDING ADAPTOR for round or square tubing  
To suit all bolt hole fixing castors. See page 7

NOTE: All dimensions are in mm and all loadings in kg unless otherwise stated