






VARLEY



- Double ball race swivel head
- Top plate or bolt hole fixing


V40V
V41V V42V

V40V + GREY RUBBER TYRED WHEEL WITH POLYPROPYLENE CENTRE - PLATE FIXING



wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type	swivel + total stop brake		
						swivel	fixed	total stop brake
80	25	108	36	50	roller	V40V 080 GRR P04	V41V 080 GRR P04	V42V 080 GRR P04
100	27	128	36	70	roller	V40V 100 GRR P04	V41V 100 GRR P04	V42V 100 GRR P04
125	30	151	36	100	roller	V40V 125 GRR P04	V41V 125 GRR P04	V42V 125 GRR P04
160	33	197	55	150	roller	V40V 160 GRR P05	V41V 160 GRR P05	V42V 160 GRR P05
200	50	235	55	205	roller	V40V 200 GRR P05	V41V 200 GRR P05	V42V 200 GRR P05

V40V + GREY RUBBER TYRED WHEEL WITH POLYPROPYLENE CENTRE - BOLT HOLE FIXING



wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type	swivel + total stop brake		
						swivel	fixed	total stop brake
100	27	128	36	70	roller	V40V 100 GRR B12		V42V 100 GRR B12
125	30	151	36	100	roller	V40V 125 GRR B12		V42V 125 GRR B12



EXPANDING ADAPTOR for round or square tubing
To suit all bolt hole fixing castors. See page 7

NOTE: All dimensions are in mm and all loadings in kg unless otherwise stated