


V40V

V41V V42V



- Double ball race swivel head
- Top plate or bolt hole fixing


VARLEY




V40V + RUBBER TYRED WHEEL WITH PRESSED STEEL CENTRE - PLATE FIXING



80, 100, 125mm




160, 200mm



wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type	fixing options		
						swivel	fixed	swivel + total stop brake
80	27	108	36	50	roller	V40V 080 SRR P04	V41V 080 SRR P04	V42V 080 SRR P04
100	27	128	36	70	roller	V40V 100 SRR P04	V41V 100 SRR P04	V42V 100 SRR P04
125	32	151	36	100	roller	V40V 125 SRR P04	V41V 125 SRR P04	V42V 125 SRR P04
160	30	197	55	150	roller	V40V 160 SRR P05	V41V 160 SRR P05	V42V 160 SRR P05
200	40	235	55	205	roller	V40V 200 SRR P05	V41V 200 SRR P05	V42V 200 SRR P05

V40V + RUBBER TYRED WHEEL WITH PRESSED STEEL CENTRE - BOLT HOLE FIXING



wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type	fixing options		
						swivel	fixed	swivel + total stop brake
100	27	128	36	70	roller	V40V 100 SRR B12		V42V 100 SRR B12
125	32	151	36	100	roller	V40V 125 SRR B12		V42V 125 SRR B12



EXPANDING ADAPTOR for round or square tubing
To suit all bolt hole fixing castors. See page 7

NOTE: All dimensions are in mm and all loadings in kg unless otherwise stated