


V60V | TR | PLATE FIXING

GREY THERMOPLASTIC RUBBER TYRED WHEEL WITH NYLON CENTRE




wheel diameter	tread width	fitted height	swivel offset *	load capacity	bearing type	swivel	fixed	swivel + total-stop brake
80	32	112.5	32 / 38	80	ball	V60V 080 TRJ P04		V62V 080 TRJ P04
100	32	135	38 / 43.5	90	ball	V60V 100 TRJ P04		V62V 100 TRJ P04
125	32	160	41	110	ball	V60V 125 TRJ P04		V62V 125 TRJ P04
150	32	184.5	45 / 36	130	ball	V60V 150 TRJ P04		V62V 150 TRJ P04

i * On certain sizes, swivel offsets differ between swivel and braked castor. Dimensions given are swivel / braked

V60V | TR | SINGLE HOLE FIXING

GREY THERMOPLASTIC RUBBER TYRED WHEEL WITH NYLON CENTRE



wheel diameter	tread width	fitted height	swivel offset *	load capacity	bearing type	swivel	fixed	swivel + total-stop brake
80	32	112.5	32 / 38	80	ball	V60V 080 TRJ B12		V62V 080 TRJ B12
100	32	135	38 / 43.5	90	ball	V60V 100 TRJ B12		V62V 100 TRJ B12
125	32	160	41	110	ball	V60V 125 TRJ B12		V62V 125 TRJ B12
150	32	184.5	45 / 36	130	ball	V60V 150 TRJ B12		V62V 150 TRJ B12

i * On certain sizes, swivel offsets differ between swivel and braked castor. Dimensions given are swivel / braked



EXPANDING ADAPTOR
for round or square tube

To suit all bolt hole fixing castors

See page 17

i All dimensions are in **mm** and all loadings are in **kg** unless otherwise stated