


- Double ball race swivel head
- Top plate or bolt hole fixing




V70V + POLYURETHANE TYRED WHEEL WITH NYLON CENTRE - PLATE FIXING



wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type	fixing		
						swivel	fixed	swivel + total stop brake
75	30	109	34	100	ball	V70V 075 PNJ P04	V71V 075 PNJ P04	V72V 075 PNJ P04
100	30	135	34	150	ball	V70V 100 PNJ P04	V71V 100 PNJ P04	V72V 100 PNJ P04
125	30	160	34	170	ball	V70V 125 PNJ P04	V71V 125 PNJ P04	V72V 125 PNJ P04

V70V + POLYURETHANE TYRED WHEEL WITH NYLON CENTRE - BOLT HOLE FIXING



wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type	fixing		
						swivel	fixed	swivel + total stop brake
75	30	109	34	100	ball	V70V 075 PNJ B12	V71V 075 PNJ B12	V72V 075 PNJ B12
100	30	135	34	150	ball	V70V 100 PNJ B12	V71V 100 PNJ B12	V72V 100 PNJ B12
125	30	160	34	170	ball	V70V 125 PNJ B12	V71V 125 PNJ B12	V72V 125 PNJ B12

EXPANDING ADAPTOR for round or square tubing
To suit all bolt hole fixing castors. See page 20



CHROME FINISH
Add C to castor reference



NOTE: All dimensions are in mm and all loadings in kg unless otherwise stated