


## V70V | TR | PLATE FIXING


GREY THERMOPLASTIC RUBBER TYRED WHEEL WITH NYLON CENTRE



	wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type	swivel	fixed	swivel + total-stop brake
<b>P</b>	75	30	105	34	80	ball	V70V 075 TRJ P04	V71V 075 TRJ P04	V72V 075 TRJ P04
<b>P</b>	100	30	130	34	100	ball	V70V 100 TRJ P04	V71V 100 TRJ P04	V72V 100 TRJ P04
<b>P</b>	125	30	156	30	120	ball	V70V 125 TRJ P04	V71V 125 TRJ P04	V72V 125 TRJ P04

## V70V | TR | SINGLE HOLE FIXING

GREY THERMOPLASTIC RUBBER TYRED WHEEL WITH NYLON CENTRE



	wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type	swivel	fixed	swivel + total-stop brake
<b>P</b>	75	30	102	34	80	ball	V70V 075 TRJ B12		V72V 075 TRJ B12
<b>P</b>	100	30	128	34	100	ball	V70V 100 TRJ B12		V72V 100 TRJ B12
<b>P</b>	125	30	155	30	120	ball	V70V 125 TRJ B12		V72V 125 TRJ B12



EXPANDING ADAPTOR  
for round or square tube

To suit all bolt hole fixing castors

See page 17

**P** Preferred range product, see page 1 for details

**i** All dimensions are in **mm** and all loadings are in **kg** unless otherwise stated