


VSL | AR | PLATE FIXING


BLACK RUBBER TYRED WHEEL WITH ALUMINIUM CENTRE



	wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type	swivel	fixed	swivel + total-stop brake
P	100	40	135	20	160	ball	VSL 100 ARJ P05	VSLF 100 ARJ P05	VSL 100 ARJ P05 SWB
P	125	50	159	30	200	ball	VSL 125 ARJ P05	VSLF 125 ARJ P05	VSL 125 ARJ P05 SWB
P	150	50	189	39	300	ball	VSL 150 ARJ P05	VSLF 150 ARJ P05	VSL 150 ARJ P05 SWB
P	200	50	238	39.5	400	ball	VSL 200 ARJ P05	VSLF 200 ARJ P05	VSL 200 ARJ P05 SWB

VSL | AP | PLATE FIXING

POLYURETHANE TYRED WHEEL WITH ALUMINIUM CENTRE



	wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type	swivel	fixed	swivel + total-stop brake
P	100	50	135	20	350	ball	VSL 100 APJ P05	VSLF 100 APJ P05	VSL 100 APJ P05 SWB
P	125	50	159	30	400	ball	VSL 125 APJ P05	VSLF 125 APJ P05	VSL 125 APJ P05 SWB
P	150	50	189	39	550	ball	VSL 150 APJ P05	VSLF 150 APJ P05	VSL 150 APJ P05 SWB
P	200	50	238	39.5	600	ball	VSL 200 APJ P05	VSLF 200 APJ P05	VSL 200 APJ P05 SWB



WHEEL BRAKE
Swivel castors only

Simple side-mounted, foot operated brake acts upon the wheel only

Add **BK** to castor reference



4-WAY DIRECTIONAL LOCK for straight line travel

To suit all swivel castors except with total-stop brake

Add **DL** to castor reference

P Preferred range product, see page 1 for details

i All dimensions are in **mm** and all loadings are in **kg** unless otherwise stated