


VSL | NY | PLATE FIXING


NYLON WHEEL



	wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type	swivel	fixed	swivel + total-stop brake
P	100	40	135	20	300	ball	VSL 100 NYJHD P05	VSLF 100 NYJHD P05	VSL 100 NYJHD P05 SWB
P	125	45	159	30	400	ball	VSL 125 NYJHD P05	VSLF 125 NYJHD P05	VSL 125 NYJHD P05 SWB
P	150	50	189	39	500	ball	VSL 150 NYJHD P05	VSLF 150 NYJHD P05	VSL 150 NYJHD P05 SWB
P	200	57	238	39.5	800	ball	VSL 200 NYJHD P05	VSLF 200 NYJHD P05	VSL 200 NYJHD P05 SWB

VSL | NP | PLATE FIXING

GREY POLYURETHANE TYRED WHEEL WITH NYLON CENTRE



	wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type	swivel	fixed	swivel + total-stop brake
P	100	40	135	20	300	ball	VSL 100 NPJ P05	VSLF 100 NPJ P05	VSL 100 NPJ P05 SWB
P	125	45	159	30	400	ball	VSL 125 NPJ P05	VSLF 125 NPJ P05	VSL 125 NPJ P05 SWB
P	150	50	189	39	500	ball	VSL 150 NPJ P05	VSLF 150 NPJ P05	VSL 150 NPJ P05 SWB
P	200	57	238	39.5	600	ball	VSL 200 NPJ P05	VSLF 200 NPJ P05	VSL 200 NPJ P05 SWB



WHEEL BRAKE
Swivel castors only

Simple side-mounted, foot operated brake acts upon the wheel only

Add **BK** to castor reference



4-WAY DIRECTIONAL LOCK for straight line travel

To suit all swivel castors except with total-stop brake

Add **DL** to castor reference

P Preferred range product, see page 1 for details

i All dimensions are in **mm** and all loadings are in **kg** unless otherwise stated