

	wheel diameter	tread width	hub width	bore diameter	load capacity	used in castor series	ball bearing
P	100	50	60	20	350	V50Q VSL VSH 2VSH	K 100 NYJ 20
P	125	50	60	20	700	V50Q VSL VSH 2VSH	K 125 NYJ 20
P	150	50	60	20	800	VSL VSH 2VSH	K 150 NYJ 20
P	160	50	60	20	850	V50Q	K 160 NYJ 20
P	200	50	60	20	1200	V50Q VSL VSH 2VSH	K 200 NYJ 20
P	250	50	60	20	1200	V50Q VSL VSH 2VSH	K 250 NYJ 20



	wheel diameter	tread width	hub width	bore diameter	load capacity	used in castor series	ball bearing
P	100	40	40	15	300	V50Q VSL VSH 2VSH	A 100 NPJ 15 - GREY
P	125	45	49	20	400	V50Q VSL VSH 2VSH	A 125 NPJ 20 - GREY
P	150	50	55	20	500	VSL VSH 2VSH	A 150 NPJ 20 - GREY
P	160	50	55	20	500	V50Q	A 160 NPJ 20 - GREY
P	200	57	60	20	800	V50Q VSL VSH 2VSH	A 200 NPJ 20 - GREY



	wheel diameter	tread width	hub width	bore diameter	load capacity	used in castor series	ball bearing
P	100	35	45	20	160	V50Q VSL VSH 2VSH	G 100 ARJ 20
P	125	48	60	20	200	V50Q VSL VSH 2VSH	G 125 ARJ 20
P	150	42	60	20	300	VSL VSH 2VSH	G 150 ARJ 20
P	160	42	60	20	350	V50Q	G 160 ARJ 20
P	200	37	60	20	400	V50Q VSL VSH 2VSH	G 200 ARJ 20
P	250	40	60	25	550	V50Q VSH 2VSH	G 250 ARJ 25



P Preferred range product, see page 1 for details

i All dimensions are in mm and all loadings are in kg unless otherwise stated