

V40Q

DOUBLE BALL RACE SWIVEL HEAD | SWIVEL HEAD SEAL




PRESSED STEEL CASTORS


V40Q | GN | PLATE FIXING

GREY RUBBER TYRED WHEEL WITH NYLON CENTRE

80, 100, 125




160, 200



	wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type	swivel	fixed	swivel + total-stop brake
P	80	40	105	34	100	roller	V40Q 080 GNR P04	V41Q 080 GNR P04	V42Q 080 GNR P04
P	100	40	128	34	160	roller	V40Q 100 GNR P04	V41Q 100 GNR P04	V42Q 100 GNR P04
P	125	40	155	34	200	roller	V40Q 125 GNR P04	V41Q 125 GNR P04	V42Q 125 GNR P04
P	160	50	195	53	350	ball	V40Q 160 GNJ P05	V41Q 160 GNJ P05	V42Q 160 GNJ P05
P	200	50	235	53	400	ball	V40Q 200 GNJ P05	V41Q 200 GNJ P05	V42Q 200 GNJ P05

V40Q | GN | SINGLE HOLE FIXING

GREY RUBBER TYRED WHEEL WITH NYLON CENTRE



	wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type	swivel	fixed	swivel + total-stop brake
P	80	40	105	34	100	roller	V40Q 080 GNR B12		V42Q 080 GNR B12
P	100	40	128	34	160	roller	V40Q 100 GNR B12		V42Q 100 GNR B12
P	125	40	155	34	200	roller	V40Q 125 GNR B12		V42Q 125 GNR B12
P	160	50	195	53	350	ball	V40Q 160 GNJ B12		V42Q 160 GNJ B12
P	200	50	235	53	400	ball	V40Q 200 GNJ B12		V42Q 200 GNJ B12



EXPANDING ADAPTOR
for round or square tube

To suit all bolt hole fixing castors

See page 17

P Preferred range product, see page 1 for details

i All dimensions are in **mm** and all loadings are in **kg** unless otherwise stated